

6.2.3	System Types as Variable Names in Proxies.	36
6.2.4		

2 Known Issues

Learn about known issues and workarounds.

1

CR#	Description
-----	-------------





CR#	Description
-----	-------------

CR#	Description
-----	-------------

CR#	Description
-----	-------------

Workaround:



3 Product Compatibilities

5 Documentation Updates and Clarifications

Read about corrections and clarifications to released documentation for PowerBuilder 12.6.

Table 22: PowerBuilder Documentation Issues

--



CR#	Description
-----	-------------

Returns

Long. Valid values are 0 for success and 50 for failure.

Usage

For basic authentication, a request is made to the XML Web service method without initially attempting to authenticate the user.

- If the XML Web service allows anonymous access, then the XML Web service method executes.
- If anonymous access is disallowed, a 401 HTTP return code is sent to the client.

In response, the proxy class returns the authentication credentials to the Web server. If the client is authenticated and subsequently authorized to access the XML Web service, the XML Web service method is executed; otherwise the client is denied access.

To summarize, any call to a Web service's method generates at least one 401 error for basic authentication.



5. Otherwise, the initial directory is the personal files directory of the current user.
- 6.



6 Migration Information

You can migrate a PowerBuilder application from any version of PowerBuilder directly to

- For .NET Windows Forms projects, select *Full*

6.2.2.2 Creating a Client Application for an EAServer 6.x EJB Component

6.2.4 OLE DB Performance with Microsoft SQL Server

In PowerBuilder 10.5.2 and later, when you use the OLE DB database interface with a Microsoft SQL Server database and retrieve data into a DataWindow, or use an embedded SQL cursor in a SELECT statement, server-side cursors help to support multiple command execution.

i Note



www.sap.com/contactsap